



Technical Data

Material:  
 Pin(outer sleeve):Brass,machined CuZn38Pb2  
 Plating(outer sleeve):  
 Tin Plated:2μm/80μm"NI, 5μm/200μ"Sn  
 Gold Plated:2μm"/80μm"Ni, 0.8μ" gold  
 Insuiator:PPS UL94V-0

Electrical:  
 Current rating:3Amps/contact max.  
 Contact resistance:≤4mΩ/contact  
 Insuiation resistance:≥1000MΩ at V=100V  
 Dlelectric Withstanding Voltage:1000V AV Min  
 Operaling voitage:60VAC/DC

Mechanical:  
 Operaling temperature:-40° C to+105° C  
 Soldering temperature:+255° C

Serial number	No. of Positions	PART NO	A	B
1	6	STOD3-I106XX1275A	7.62	5.08
2	8	STOD3-I108XX1275A	10.16	7.62
3	10	STOD3-I110XX1275A	12.7	10.16
4	12	STOD3-I112XX1275A	15.24	12.7
5	14	STOD3-I114XX1275A	17.78	15.24
6	16	STOD3-I116XX1275A	20.32	17.78
7	18	STOD3-I118XX1275A	22.86	20.32
8	20	STOD3-I120XX1275A	25.4	22.86
9	22	STOD3-I122XX1275A	27.94	25.4
10	24	STOD3-I124XX1275A	30.48	27.94
11	28	STOD3-I128XX1275A	35.56	33.02

TOLERANCE:

X.	±XXX
.X	±0.20
.XX	±0.10
ANG.	



上海狮拓电子科技有限公司

產品名稱:  
 產品料號:

THIRD ANGLE PROJECTION

簽名 \_\_\_\_\_  
 日期 \_\_\_\_\_  
 審核 \_\_\_\_\_  
 日期 \_\_\_\_\_

客戶確認

承認 \_\_\_\_\_ 日期 \_\_\_\_\_  
 駁回 \_\_\_\_\_ 日期 \_\_\_\_\_