



Technical Data

Material:

Pin(outer sleeve):Brass,machined CuZn38Pb2

Plating(outer sleeve):

Tin Plated:2 μ m/80 μ m"NI, 5 μ m/200 μ "Sn

Gold Plated:2 μ m"/80 μ m"Ni, 0.8 μ " gold

Insuiator:PPS UL94V-0

Electrical:

Current rating:3Amps/contact max.

Contact resistance: $\leq 4m\Omega$ /contact

Insuiation resistance: $\geq 1000M\Omega$ at V=100V

Dleictric Withstanding Voltage:1000V AV Min

Operaling voitage:60VAC/DC

Mechanical:

Operaling temperature:-40 $^{\circ}$ C to+105 $^{\circ}$ C

Soldering temperature:+255 $^{\circ}$ C

Serial number	No. of Positions	PART NO	A	B
17	24	D5-I124XX1370A	30.48	27.94
18	28	D5-I128XX1370A	35.56	33.02
19	32	D5-I132XX1370A	40.64	38.1
20	36	D5-I136XX1370A	45.72	43.18
21	40	D5-I140XX1370A	50.8	48.26
22	42	D5-I142XX1370A	53.34	50.8
23	48	D5-I148XX1370A	60.96	58.42
24	50	D5-I150XX1370A	63.5	60.96
25	52	D5-I152XX1370A	66.04	63.5

TOLERANCE:

X. $\pm XXX$

.X ± 0.20

.XX ± 0.10

ANG.



上海狮拓电子科技有限公司

產品名稱:

產品料號:

THIRD ANGLE PROJECTION



簽名 _____

日期 _____

審核 _____

日期 _____

客戶確認

承認 _____ 日期 _____

駁回 _____ 日期 _____