




P. C. B LAYOUT

PART NO	Pin Length H
STOD2-DXXXXXX0920B	6.00
STOD2-DXXXXXX1020B	7.00
STOD2-DXXXXXX1120B	8.00
STOD2-DXXXXXX1220B-2	9.00
STOD2-DXXXXXX1320B	10.00
STOD2-DXXXXXX1420B	11.00
STOD2-DXXXXXX1520B	12.00
STOD2-DXXXXXX1620B	13.00
STOD2-DXXXXXX1780B-3	13.60
STOD2-DXXXXXX1820B	15.00



Technical Data

Material:

Pin(outer sleeve):Brass,machined CuZn38Pb2

Plating(outer sleeve):

Tin Plated:2μm/80μm"NI, 5μm/200μ"Sn

Gold Plated:2μm"/80μm"Ni, 0.8μ" gold

Plating(Contact):2μm/80μ"NI,gold or Tin plated

Insulator:PPS UL94V-0

Clip(Contact 4 Flnger):Beryllium copper,heat teated

Electrical:

Current rating:3Amps/contact max.

Contact resistance:≤4mΩ/contact

Insuation resistance:≥1000MΩ at V=100V

Operaing voitage:60VAC/DC

Mechanical:

Average Insertion force with steel pin of Ø0.432:<250g

Average withdrawal force with steel pin of Ø0.432:>70g

Mechanical lige cycle:min 200

Operaling temperature:-40° C to+105° C

Soldering temperature:+255° C

TOLERANCE:

.X ±XXX

.X ±0.20

.XX ±0.10

ANG.



產品名稱:

產品料號:

上海狮拓电子科技有限公司

THIRD ANGLE PROJECTION



簽名

日期

審核

日期

客戶確認

☐ 承認 日期

☐ 駁回 日期

STOD2-DXXXXXX1100B